

Track Max Hydraulic Flat Tappet Camshaft and Camshaft/Lifter Kits for Small Block Chevrolet

2019

Part Number	Characteristics	Duration @ .050"	Valve Lift w/1.5 Ratio Rocker Arms	Lobe Sep.	Recommended Valve Springs	Recommended Valve Spring Retainers	Recommended Valve Locks	Recommended Valve Spring Upgrade Kits
TFS-31401000 [†] TFS-K31401000 [‡]	Good idle, strong low-end torque, 2,200-5,700 RPM powerband. Small tube headers and low-restriction exhaust recommended. Compression: 9:1 minimum.	212°/214°	.443"/.449"	110°	TFS-16942-16	TFS-51400423	TFS-31400443	TFS-K16942
TFS-31401001 [†] TFS-K31401001 [‡]	Fair idle, strong midrange power, 2,600-6,100 RPM powerband. 2,500-3,000 RPM stall converter. Compression: 9.5:1 minimum.	226°/234°	.480"/.495"	110°	TFS-16981-16	TFS-31400423	TFS-31400443	TFS-K16981
TFS-31401002 [†] TFS-K31401002 [‡]	Rough idle, excellent top-end power, 3,500-6,700 RPM powerband. 3,000-3,500 RPM stall converter. Compression: 10:1 minimum.	246°/254°	.510"/.518"	112°	TFS-16838-16	TFS-51400423	TFS-31400443	TFS-K16838

*Roller rocker arms recommended ^Titanium retainers †Camshaft only ‡Kit